

Nitrite Assay Kit

ARG83399 Nitrite Assay Kit can be used to measure Nitrite in serum, plasma, urine, tissue extracts, cell lysate, cell culture media and other biological fluids.

Catalog number: ARG83399

Package: 96 wells

For research use only. Not for use in diagnostic procedures.

TABLE OF CONTENTS

SECTION	Page
INTRODUCTION	3
PRINCIPLE OF THE ASSAY	3
MATERIALS PROVIDED & STORAGE INFORMATION	3
MATERIALS REQUIRED BUT NOT PROVIDED	4
TECHNICAL HINTS AND PRECAUTIONS	4
SAMPLE COLLECTION & STORAGE INFORMATION	4
REAGENT PREPARATION	4
ASSAY PROCEDURE	6
CALCULATION OF RESULTS	7
EXAMPLE OF TYPICAL RESULT	8

MANUFACTURED BY:

Arigo Biolaboratories Corporation

Address: 9F.-7, No. 12, Taiyuan 2nd St., Zhubei City,

Hsinchu County 302082, Taiwan

Tel: +886-3-6221320

Fax: +886-3-5530266

Email: info@arigobio.com

INTRODUCTION

Nitrite can be reduced to nitric oxide or ammonia by many species of bacteria. Under hypoxic conditions, nitrite may release nitric oxide, which causes potent vasodilation. Several mechanisms for nitrite conversion to NO have been described, including enzymatic reduction by xanthine oxidoreductase, nitrite reductase, and NO synthase (NOS), as well as nonenzymatic acidic disproportionation reactions.

PRINCIPLE OF THE ASSAY

The ARG83399 Nitrite Assay Kit determined Nitrite by nitrite is reduced to Nitrogen Oxide using Griess Reagent I. Then, Nitrogen Oxide reacts with Griess Reagent II forming a stable product. The increase in absorbance at 540 nm is directly proportional to the enzyme activity.

MATERIALS PROVIDED & STORAGE INFORMATION

Store the unopened kit at 2-8°C. Use the kit before expiration date.

Component	Quantity	Storage
Microplate	1 X 96-well plate	
Standard	1 vial (lyophilized)	4°C
Reaction Dye Diluent	3 ml	4°C
Reaction Dye A	1 vial (lyophilized)	4°C (protect from light)
Reaction Dye B	1 vial (lyophilized)	4°C (protect from light)
Assay Buffer A	30 ml	4°C
Assay Buffer B	30 ml	4°C

MATERIALS REQUIRED BUT NOT PROVIDED

- Microplate reader capable of measuring absorbance at 540nm
- Pipettes and pipette tips
- Deionized or distilled water

TECHNICAL HINTS AND PRECAUTIONS

- Wear protective gloves, clothing, eye, and face protection especially while handling blood or body fluid samples.
- Store all component at 4°C. Reaction Dye A and B should protect from light.
- Briefly spin down the reagents before use.
- It is highly recommended that the standards and samples be assayed in at least duplicates.
- Change pipette tips between the addition of different reagent or samples.

SAMPLE COLLECTION & STORAGE INFORMATION

The sample collection and storage conditions listed below are intended as general guidelines. Sample stability has not been evaluated.

<u>For tissue</u>- Weigh out 0.1 g tissue, homogenize with 0.5 ml distilled water, transfer all samples into centrifuge tube, add 0.25 ml Assay Buffer A, mix; then add 0.25 ml Assay Buffer B, mix; centrifuged at 10,000g 4 °C for 10 minutes, take the supernatant into a new centrifuge tube for detection

<u>For liquid</u>- Add 0.5 ml samples into centrifuge tube, add 0.25 ml Assay Buffer A, mix; then add 0.25 ml Assay Buffer B, mix; centrifuged at 10,000g 4 °C for 10 minutes, take the supernatant into a new centrifuge tube for detection.

REAGENT PREPARATION

- Standard: Add 1 ml of distilled water to yield stock, then add 10 μl standard into 990 μl distilled water to yield standard stock, then add 1 μl stock into 999 μl distilled water to yield 1 nmol/ml standard. Perform 2-fold serial dilution of the top standards to make the standard curve.
- Reaction Dye A: Reconstitute the Substrate with 2 ml of Reaction Dye
 Diluent. Allow the Substrate keep on bench for few minutes. Make sure
 the Substrate is dissolved completely and mixed thoroughly before use.
- Reaction Dye B: Reconstitute the Substrate with 1 ml of Reaction Dye
 Diluent. Allow the Substrate keep on bench for few minutes. Make sure
 the Substrate is dissolved completely and mixed thoroughly before use.
- Sample: If the measuring absorbance of samples is higher than the standard, dilute the samples with Distilled water before assay and assay again.

ASSAY PROCEDURE

Standards and samples should be assayed in at least duplicates.

- 1. Sample wells: Add **170 μl Samples** into Sample wells.
- 2. Standard wells: Add **170 μl Standard** into Standard wells.
- 3. Add **20 μl** per **Reagent Dye A** into each wells.
- 4. Mix well. Incubate at RT for 3 min.
- 5. Add 10 μl per Reagent Dye B into each wells.
- 6. Mix well. Incubate at RT for 15 min. Read the OD at 540nm.

Summary of Nitrite Assay Kit Procedure

Reagent	Sample	Standard	Blank		
Sample	170 μΙ	-	-		
Standard	-	170 μΙ	-		
Distilled water	-	-	170 μΙ		
Reagent Dye A	20 μΙ	20 μΙ	20 μΙ		
Mix well. Incubate all Sample tubes at RT oven for 3 min .					
Reagent Dye B	10 μΙ	10 μΙ	10 μΙ		
Mix well. Incubate at RT oven for 15 min.					
Read the OD with a microplate reader at 540 nm .					

CALCULATION OF RESULTS

1. Calculate the average absorbance values for each set of samples, standard and blank.

2. Calculation:

A. Definition:

C_{Standard}: the standard concentration, 1 nmol/ml;

V_{Assay}: the volume of distilled water and assay buffer, 1 ml;

W: the weight of sample, g;

 V_{Sample} : the volume of reaction sample, 170 μ l = 0.17 ml;

 $V_{standard}$: the volume of standard sample, 170 μ l = 0.17 ml;

n: dilution factor; =2

B. Formula:

a). According to the weight

```
Nitrite (nmol/g) =
```

$$[(C_{Standard}\ X\ V_{standard})\ X\ (OD_{Sample}\text{-}\ OD_{Blank})]\ /\ [(OD_{Standard}\text{-}\ OD_{Blank})\ X\ (W\ X)]$$

V_{Sample} / V_{total})]

$$= (OD_{Sample} - OD_{Blank}) / [(OD_{Standard} - OD_{Blank}) X W]$$

b). According to the volume

3. Detection range:

The detection range is from 0.01 nmol/ml- 1 nmol/ml.

4. If the samples have been diluted, the calculated concentration must be further converted by the appropriate dilution factor according to the sample preparation procedure as described above.

EXAMPLE OF TYPICAL RESULT

The following data is for demonstration only and cannot be used in place of data generations at the time of assay. Please note this data is for demonstration only and serial diluted standards are not necessary for this kit.

